

PARKANSON BANDSAWS

HEAVY DUTY SEMI-AUTO DOUBLE MITER CUTTING BANDSAW

CE



PK800DMS

PARKANSON BANDSAWS

HEAVY DUTY SEMI-AUTO DOUBLE MITER CUTTING BANDSAW

FEATURES:

1. For cutting any angle from 45° forward to 60° backward.
2. NC/Manual mitre positioning with digital readout.
3. The rotary center is at the intersection point of the saw blade and the fixed vice jaw.
4. Inclination of the saw blade (5°) to reduce the initial blade impact when cutting beams.
5. Columns with linear guideway.
6. Automatic positioning of guide arm.
7. Return of saw bow to starting cutting position or stop to bottom when cut of material.

STANDARD EQUIPMENTS

1. Variable blade speed drive
2. Hydraulic blade tension.
3. Laser liner
4. Vice pressure regulator

OPTIONAL EQUIPMENTS

1. Mist lubrication
2. Top clamp
3. Full high vise jaws
4. Roller table
5. Powered roller table
6. NC Material Feed System

SPECIFICATIONS:

| MODEL | | PK800DMS |
|-------------------------|-------------|-----------------|
| Cutting Capacity (mm) | ● 90° | 600 |
| | ■ 90° | 550x800 (HxW) |
| | ■ 45° Left | 400x520 550x480 |
| | ■ 30° Left | 400x340 550x300 |
| | ■ 45° Right | 550x520 |
| Motors | Saw blade | 5.5 kw |
| | Hydraulic | 1.5 kw |
| | Coolant | 0.2 kw |
| Blade size | | 6740x41x1.3 |
| Blade speed (M/min) | | 20-90 |
| Vice clamping width | | 80-820 mm |
| Working height (mm) | | 925 |
| Dimensions (mm) | Length | 1770 |
| | Width | 3350 |
| | Height | 2320 |
| Net weight (approx.) Kg | | 5200 |



NC Material Feed System (optional)

PK800DMS



U1/10 Renewable Chase Bibra Lake WA 6163
 Ph: 08 94109500 Fax: 08 94109555
 Website: www.capitalequipment.biz
 E-mail: mark@capitalequipment.net.au
jim@capitalequipment.net.au

