

# RDB-125

## For the Budget Minded

Based on our RDB-100, the RDB-125 is the perfect bender for the fabricator that wants a powered bender on a budget.

- ◆ Low Pressure Industrial Grade Hydraulic System
- ◆ Uses Standard Baileigh Industrial Drop on Die Sets for fast tooling changes
- ◆ Replaceable Bronze Bushings at all pivot points with grease zerks
- ◆ Anti-Spring back mechanism included
- ◆ Integrated Degree Dial with bend indicator Included
- ◆ Infinite Tooling possibilities



### Specifications

Mild Steel Pipe (Schedule 40)	2.00"	60 mm x 4 mm
Aluminum Pipe (Schedule 40)	2.00"	60 mm x 4 mm
Stainless Steel Pipe (Schedule 40)	1.50"	48 mm x 3 mm
Mild Steel Round Tube (Wall)	2.50" (.125)	64 mm x 3 mm
Aluminum Round Tube (Wall)	2.50" (.156)	64 mm x 4 mm
Stainless Steel Round Tube (Wall)	2.375" (.125)	60 mm x 3 mm
Chromolly Round Tube (Wall)	2.00" (.125)	50 mm x 3 mm
Mild Steel Solid Rod	1.25"	32 mm
Mild Steel Square Tube (Wall)	2.00" (.125)	50 mm x 3 mm
Minimum OD	.25"	6 mm
Maximum Speed to 180 Degrees	N/A	N/A
Maximum Center Line Radius (CLR)*	10.50"	267 mm
Minimum CLR	.50"	13 mm
Power Requirements	110V	220V, 1Ph, 50Hz
Weight (Lbs.)	350	160 kg.
Length	42.00"	1067 mm
Width	22.00"	560 mm
Height	42.00"	1067 mm

\*Maximum CLR dependant on material outside diameter.  
Specifications subject to change without notice.