

RDB-250

More Bang for the Buck

The RDB-250 is the first in Baileigh Industrial's line of Computer Controlled Tube and Pipe Benders. It offers features that only benders double the price have.

- ◆ Computer programmable
- ◆ Touch-screen programmer holds 170 Jobs with 10 bends per job
- ◆ Can bend 360 Degrees left or right (with optional tooing)
- ◆ Six Bending speeds
- ◆ Fast, 9 Seconds to 180 Degrees
- ◆ 9.0" (229 mm) Maximum Centerline Radius
- ◆ Accepts Optional Positioning table
- ◆ Portable



Specifications		
Mild Steel Pipe (Schedule 40)	2.00"	60 mm x 4 mm
Aluminum Pipe (Schedule 40)	2.00"	60 mm x 4 mm
Stainless Steel Pipe (Schedule 40)	1.50"	48 mm x 3mm
Mild Steel Round Tube (Wall)	2.50" (.125)	64 mm x 3 mm
Aluminum Round Tube (Wall)	2.50" (.156)	64 mm x 4 mm
Stainless Steel Round Tube (Wall)	2.375" (.125)	60 mm x 3 mm
Chromolly Round Tube (Wall)	2.00" (.125)	50 mm x 3 mm
Mild Steel Solid Rod	1.25"	32 mm
Mild Steel Square Tube (Wall)	2.00" (.125)	50 mm x 3 mm
Minimum OD	.25"	6 mm
Maximum Speed to 180 Degrees	9 Sec.	9 Sec.
Maximum Center Line Radius (CLR)*	9.00"	229 mm
Minimum CLR	.50"	13 mm
Power Requirements	220V (1Ph)	220V, 1Ph, 50Hz
Weight (Lbs.)	610	278 kg.
Length	40.00"	1016 mm
Width	32.00"	813 mm
Height	43.00"	1092 mm

*Maximum CLR dependant on material outside diameter.
Specifications subject to change without notice.