

HYDRAULIC SWING BEAM SHEARS



Model	Shear Size (TXW) (mm)	Shear Angle	No Load Stroke	Adjustment Range of Back Gauge (mm)	Main Motor Power (KW)	Weight (KG)	Dimensions (mm) LXWXH	Min Shearing Thickness (mm)	Back Gauge Motor Power (KW)	Throat Depth (mm)	Working Table Height (mm)
TW4X2000	4X2000	1°30'	18	20-600	7.5	3800	2590X1520X1450	0.5	0.55	140	650
TW4X2500	4X2500	1°30'	18	20-600	7.5	4200	3140X1520X1450	0.5	0.55	140	650
TW6X2000	6X2000	1°30'	18	20-600	7.5	5000	2640X1610X1620	0.5	0.55	140	800
TW6X2500	6X2500	1°30'	18	20-600	7.5	6000	3140X1610X1620	0.5	0.55	140	800
TW6X3200	6X3200	1°30'	14	20-600	7.5	7200	4010X1610X1620	0.5	0.55	140	800
TW6X4000	6X4000	1°30'	10	20-600	7.5	10000	4640X1705X1700	0.5	0.55	140	800
TW6X5000	6X5000	1°30'	9	20-800	15	15000	5725X2160X1900	0.5	0.55	140	800
TW8X2500	8X2500	1°30'	14	20-600	11	6500	3140X1610X1620	0.5	0.55	140	800
TW8X3200	8X3200	1°30'	10	20-600	11	7800	4010X1610X1620	0.5	0.55	140	800
TW8X4000	8X4000	1°30'	8	20-600	11	11000	4680X1705X1700	1	0.55	140	800
TW10X2500	10X2500	1°48'	12	20-600	15	8000	3350X2050X1790	1	0.55	140	800
TW10X3200	10X3200	1°48'	10	20-600	15	10000	4050X2050X1790	1	0.55	140	800
TW10X4000	10X4000	1°48'	8	20-600	18.5	14000	4920X2250X2050	1	0.55	80	900
TW12X2500	12X2500	1°48'	12	20-800	18.5	11000	3320X2050X1800	1	0.55	140	800
TW12X3200	12X3200	1°48'	10	20-800	18.5	12500	3350X2050X1800	1	0.55	140	800
TW12X4000	12X4000	2°	8	20-800	18.5	16000	4920X2250X2050	1	0.55	80	800
TW16X2500	16X2500	2°	7	20-800	22	15000	3300X2300X2100	1	0.55	170	800
TW16X3200	16X3200	2°	7	20-800	22	16000	4100X2300X2100	1	0.55	170	800
TW16X4000	16X4000	2°	6	20-800	20	20000	4800X2300X2100	1	0.55	170	800
TW20X2500	20X2500	2°	8	20-800	30	16000	3300X2300X2205	1	0.55	170	800
TW20X3200	20X3200	2°	5	20-800	30	20000	4000X2300X2205	1	0.55	170	800
TW20X4000	20X4000	2°30'	4	20-800	30	23000	4840X3190X2400	1	0.55	170	910



**CAPITAL EQUIPMENT
MACHINERY SALES**

Capital Equipment Machinery Sales
1/10 Renewable Chase
Bibra Lake WA 6163
Ph: (08) 9410 9500
Fax: (08) 9410 9555