

## **TW2280**





Capital Equipment Machinery Sales 1/10 Renewable Chase Bibra Lake WA 6163

Ph: (08) 9410 9500 Fax: (08) 9410 9555

www.capitalequipment.net.au

## CAPITAL LATHES

Model	TW2280	1
Capacity		1
Swing Over Bed	560mm	<ul> <li>Standard Accessories</li> <li>Three jaw chuck</li> <li>Four jaw chuck</li> <li>Face plate</li> <li>Coolant system</li> <li>Foot brake</li> <li>Thread chasing dial</li> <li>Work light</li> <li>Rear splash guard</li> <li>Quick change tool post</li> <li>Operation manual</li> <li>Taper turning attachment</li> <li>2 axis DRO</li> </ul>
Swing Over Cross Slide	350mm	
Swing In Gap	785mm	
Centre Height	280mm	
Distance Between Centres	2000mm	
Width Of Bed	350mm	
Max. Section Of Tool	25x25mm	
Max. Travel Of Cross Slide	316mm	
Max. Travel Of Compound Rest	130mm	
Headstock		
Spindle Bore	105mm	
Spindle Nose	D1-8	
Taper Of Spindle Bore	MT #7	
Spindle Speed Step	12	
Range Of Spindle Speed	25-1600rpm	
Feeds And Threads		
Longitudinal Feed Range (mm/rev)	0.059-1.646	
Cross Feed Range (mm/rev)	0.020-0.573	
Tailstock		
Travel Of Tailstock Sleeve	180mm	
Dia. Of Tailstock Sleeve	75mm	
Morse Taper Of Tailstock Sleeve	MT #5	
Motor		
Power Of Main Motor	7.5kW	
Voltage	415V 3 phase	
Weight And Dimensions		
Machine Space Required (LxWxH)	340 x 112 x 143mm	
Net Weight	2560kg	



CAPITAL EQUIPMENT MACHINERY SALES

Capital Equipment Machinery Sales 1/10 Renewable Chase Bibra Lake WA 6163

Ph: (08) 9410 9500 Fax: (08) 9410 9555

www.capitalequipment.net.au