

Cold Water High Pressure Cleaners

Industrial Models - Single Phase



Technical Data	
Part number	K2160TST-10A
Operating pressure, continuously adjustable	30-120 bar, 435-1740psi
Max. admissible overpressure	150bar, 2175psi
Water output	11L/min.
Inlet water temperature	max. 60°C
Suction height	2.5m
Nozzle size, Dirtkiller	042
Nozzle size, Flat jet nozzle	042
Motor speed	1400rpm
Connected load	230V, 10A, 50 Hz
Power intake	3.2kW
Power output	2.4kW
Weight	39.5kg
Dimensions (L x W x H) in mm	375 x 360 x 900

Features and Equipment	
Total-Stop System	•
Low pressure detergent	•
Steel braided high-pressure hose, 10m NW 6	•
Trigger gun with safety catch 'Midi'	•
Dirtkiller lance with stainless steel pipe + nozzle	•
Vario-jet lance with stainless steel pipe	•
Flat-jet lance with stainless steel pipe	•
Water Intake Filter	0

The K2160TST makes short work of most industrial jobs. Packed full of features such as hose drum with 15m steel wire hose, stainless steel lances including 'Dirt Killer' turbo lance and flat jet lance and graphite packed seals for dry-run safety. This machine is designed to be your life partner in cleaning!

- Continuously adjustable pressure and quantity control
- High pressure detergent application
- Brass pump head and ceramic coated pump pistons for long life
- 1400rpm built to last a lifetime
- Single phase 10amp

Optional Accessories





Nozzle - 045 x 1/4" - Female (#410713) Lance + Nozzle - 045, 500mm (#41570)



Lance Extension ST30 x M22 - 1000mm (#41154)

Wire Braided High Pressure Hose





