






Premium performance, lifetime and ergonomics

The Gerni MC 6P industrial cold water pressure cleaners provide high cleaning performance and optimal ergonomics suitable for demanding customers in industry, heavy agriculture, shipping, transport and the food industry.


The Gerni MC 6P is equipped with the NA6 wobble disc pump with 4 ceramic pistons and robust construction optimised for intense use greater than 5 hours per day. The NA6 pump is inspired by our longest lasting and renowned pump and offers unbeatable lifetime as well as the possibility to be fed with 80°C inlet water, converting your cold water washer to a hot water unit for even greater cleaning efficiency and lowered cleaning costs.

- NA6 4 ceramic piston pump with 80°C inlet temp
- Tough and sturdy design with 30mm steel frame
- Optimal storage and transport with foldable handle and easy lifting points
- High mobility with large rear wheels and front castor wheel
- Easy accessibility to pump, optimal service concept
- Ergonomic accessory concept
- Flow activated control system
- Low pump oil safety functionWater ajustment at pump head
- 2 way chemical dosing valve
- 2 detergent tanks
- Eligible for 3 year commercial warranty (conditions apply).

• Standard equipment

Included accessories		Ref. no.	Min. required	MC 6P-250/1100FA
Ergo System Coupling and Adapter				
	NIPPLE	101119496	0	•
High Pressure Female Coupling				
	HOSE NOZZLE R/34	61369	0	•
High Pressure Hose, DN10				
	HOSE, COMP. 10M. BLACK, 3	6101766	0	•
Spray Gun				
	ERGO 2000 STANDARD W.	106403122	0	•
Tornado Lance				
	TORNADO PLUS 1120 BEND	106403010	0	•
Tornado Nozzle with Indication Ring				

Premium performance, lifetime and ergonomics

Included accessories		Ref. no.	Min. required	MC 6P-250/1100FA
	TORNADO NOZZLE 0475	301150005	0	•

Model	MC 6P-250/1100FA
Ref. no.	107146766

PRODUCT FEATURES

Detergent tank	•
Three phase	•
Pump oil warning system	•
Robust steel chassis	•
Big wheels and convenient grip	•
Parking brake	•
Adjustable handle	•
Lance and spray gun storage	•
Cable storage	•
Ceramic pistons	•
Flow-activated control system	•
NA6 - 4 ceramic piston pump	•
Delayed automatic start stop	•
2 x detergent injector	•

Technical specifications	MC 6P-250/1100FA
Pump pressure (bar/MPa)	250/25
Cleaning impact (kg/force)	6.4
Pump (RPM)	1450
Power consumption (kW)	8.3
Voltage/phase/frequency/current (V/~/Hz/A)	415/3/50/15
Water flow Qmax/Qiec (l/h)	1100/1010
El cable (m)	8
Nozzle size	.0475
Max. inlet temperature (°C)	80
Ceramic pistons	4
Length x width x height (mm)	775x570x1020
Suction height dry (m)	1
Weight (kg)	89