

CAPITAL DRILLS

CAPITAL DRILLS



DH35G
VERTICAL
DRILLING
MACHINE
WITH
AUTOFEED

Capital Equipment Machinery Sales

1/10 Renewable Chase, Bibra Lake WA 6163

Ph: 08 9410 9500 Fax: 08 9410 9555

www.capitalequipment.net.au



CAPITAL DRILLS

SPECIFICATIONS

Maximum Drilling Diameter	35mm
Taper Of Spindle Hole	MT4
Column Diameter	115mm
Maximum Travel Of Spindle	125mm
Range Of Spindle Speeds (8 Steps)	75 - 2000 rpm
Maximum Distance From Spindle Nose To Working Table	65 - 800mm
Dimensions Of Working Table	400 x 420mm
Dimensions Of Base	730 x 405mm
Width Of T-Slot	14mm
Range Of Feed (3 Steps)	0.05 - 0.15
Power Of Main Motor	1.5kW
Power Of Coolant Pump	0.1 kW
Overall Dimension (LxWxH)	860 x 474 x 2175mm
Packing Size (LxWxH)	990 x 550 x 2240mm
Weight	350kg

APPLICATION

This machine is designed for drilling, counter-boring, reaming, tapping, spot-facing, etc. The maximum drilling capacity is 35mm on small or middle sized work pieces. It is widely used in machine works and repair shops for single piece or small lot production, having the features of abundant horse- power and high rigidity when compared with all the others of its kind at home or abroad

Capital Equipment Machinery Sales

1/10 Renewable Chase, Bibra Lake WA 6163

Ph: 08 9410 9500 Fax: 08 9410 9555

www.capitalequipment.net.au